

IN THE CLAIMS

1. (Currently Amended) A thermal transfer material, comprising:
a heat spreader component, wherein the heat spreader component comprises a top surface, a bottom surface and at least one heat spreader material, and
at least one thermal interface material, wherein the thermal interface material comprises a phase change material and wherein the thermal interface material is directly deposited onto at least part of the bottom surface of the heat spreader component.
2. (Original) The thermal transfer material of claim 1, wherein the thermal material is further coupled to a substrate.
3. (Original) The thermal transfer material of claim 2, wherein the substrate comprises silicon.
4. (Original) The thermal transfer material of claim 1, wherein the thermal transfer material further comprises at least one adhesive component.
5. (Original) The thermal transfer material of claim 4, wherein the at least one adhesive component is coupled to the heat spreader component.
6. (Original) The thermal transfer material of claim 4, wherein the at least one adhesive component is coupled to the thermal interface material.
7. (Original) The thermal transfer material of claim 4, wherein the at least one adhesive component is mixed into at least some of the thermal interface material.
8. (Original) The thermal transfer material of claim 1, wherein the heat spreader component comprises a metal, a metal-based material, a high-conductivity non-metal or combination thereof.

Honeywell Docket No. H0004275.84418 US - 4018
Buchalter Docket No.: H9925-3406
Confirmation No.: 6412

9. (Original) The thermal transfer material of claim 8, wherein the heat spreader component comprises nickel, aluminum, copper or a combination thereof.
10. (Original) The thermal transfer material of claim 9, wherein the metal-based material or high-conductive non-metal comprises silicon, carbon, copper, graphite, diamond or a combination thereof.
11. (Original) The thermal transfer material of claim 10, wherein the heat spreader component comprises a thickness of about 0.25 mm to about 6 mm.
12. (Original) The thermal transfer material of claim 11, wherein the thickness is from about 0.5 mm to about 5 mm.
13. (Original) The thermal transfer material of claim 1, wherein the thermal interface material comprises a crosslinkable thermal interface material.
14. Canceled.
15. (Original) The thermal transfer material of claim 1, wherein the thermal interface material comprises a polymer solder material, a polymer solder hybrid material or a combination thereof.
16. (Original) The thermal transfer material of claim 1, wherein the thermal interface material comprises a conductive filler, a metallic material, a solder alloy and combinations thereof.
17. (Currently Amended) A method of forming a thermal transfer material, comprising:

providing a heat spreader component, wherein the heat spreader component comprises a top surface, a bottom surface and at least one heat spreader material;

providing at least one thermal interface material, wherein the thermal interface material comprises a phase change material and wherein the thermal

interface material is directly deposited onto the bottom surface of the heat spreader component; and

depositing the at least one thermal interface material onto the bottom surface of the heat spreader component.

18. (Original) The method of claim 17, wherein the thermal transfer material further comprises at least one adhesive component.
19. (Original) The method of claim 18, wherein the at least one adhesive component is coupled to the heat spreader component.
20. (Original) The method of claim 18, wherein the at least one adhesive component is coupled to the thermal interface material.
21. (Original) The method of claim 18, wherein the at least one adhesive component is mixed into at least of the thermal interface material.
22. (Original) The method of claim 17, wherein the heat spreader component comprises a metal, a metal-based material, a high-conductivity non-metal or a combination thereof.
23. (Original) The method of claim 22, wherein the heat spreader component comprises nickel, aluminum, copper or a combination thereof.
24. (Original) The method of claim 22, wherein the metal-based material or high-conductive non-metal comprises silicon, carbon, copper, graphite, diamond or a combination thereof.
25. (Original) The method of claim 17, wherein the heat spreader component comprises a thickness of about 0.25 mm to about 6 mm.
26. (Original) The method of claim 25, wherein the thickness is from about 0.5 mm to about 5 mm.
27. (Original) The method of claim 17, wherein the thermal interface material comprises a crosslinkable thermal interface material.

Honeywell Docket No. H0004275.84418 US - 4018
Buchalter Docket No.: H9925-3406
Confirmation No.: 6412

28. Canceled.
29. (Original) The method of claim 17, wherein the thermal interface material comprises a polymer solder material.
30. (Original) The method of claim 17, comprises a conductive filler, a metallic material, a solder alloy and combinations thereof.
31. (Currently Amended) A method for forming an IC package, comprising:
providing ~~[[a]]~~ the thermal transfer material of claim 1;
providing at least one adhesive component;
providing at least one surface or substrate;
coupling the at least one thermal transfer material with the at least one adhesive component to form an adhesive unit; and
coupling the adhesive unit to the at least one surface or substrate to form a thermal package.
32. (Original) The method of claim 31, further comprising coupling an additional layer or component to the thermal package.
33. Canceled.